

PRODUCT DATASHEET

SP DK FIX P 8W 930 PS DIM IP44 BK

SPOT DARKLIGHT | Recessed mounted spotlight with improved anti-glare light-comfort UGR<19, fixed



Areas of application

- Direct replacement for recessed spotlights with halogen lamps
- General illumination
- Hotel rooms and corridors
- Bars, restaurants
- Accent lighting
- Galleries, museums
- Residential interiors

Product benefits

- Darklight: Special construction for enhanced low-glare light-comfort
- Stealth appearance thanks to extra small bezel
- Powerselect: Brightness adjustment via dip switches on the driver
- Easy replacement of external driver thanks to plug with bayonet lock
- Easy installation and electrical connection thanks to tool-free electrical connectors
- SCALE Design – great appearance, valuable materials and small size fits into every surrounding
- 5 years guarantee

Product features

- Color rendering index R_a : 90
- Type of protection: IP44 (room side)
- Beam angle: 36°
- Die-cast aluminum housing
- Silicon-pad protected springs
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)




- Through-wiring possible

TECHNICAL DATA**Electrical data**


Nominal wattage	8 W / 6 W / 4 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	38.000 mA
Inrush current	2 A
Inrush current time T_{h50}	60 μ s
Max. number of luminaires per miniature circuit breaker B16	336
Max. number of luminaires per miniature circuit breaker C10	210
Max. number of luminaires per miniature circuit breaker C16	336
Power factor λ	0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	Electronic control gear (ECG)

Photometrical data

Luminous flux	680 lm / 540 lm / 340 lm
Luminous efficacy	85 lm/W
Color temperature	3000 K
Light color (designation)	Warm white
Color rendering index Ra	90
Standard deviation of color matching	≤ 3 sdc _m
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Beam angle	36 °
UGR	< 19




SP DK FIX P 8W 930 PS DIM IP44 BK



SP DK FIX P 8W 930 PS DIM IP44 BK

Dimensions & Weight

Diameter	81.00 mm
Height	54.00 mm
Product weight	250.00 g



SP DK FIX P 8W PS DIM IP44

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA
Glow Wire Test according to IEC 60695-2-12	650 °C

Mercury content	0.0 mg
-----------------	--------

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-42...+80 °C
Type of connection	Push terminal
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	68 mm
Mounting depth	60,0 mm
Adjustable	No
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	41000 h ¹⁾
Lifespan L90/B10 at 25 °C	18000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	180 mA
ECG - Output ripple current	< 5 %
ECG - Length	68.00 mm
ECG - Width	55,0 mm
ECG - Height	22,0 mm

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No

Ball shot safe	No
----------------	----

Additional product data

Added function	MULTI SELECT
----------------	--------------

EQUIPMENT / ACCESSORIES

- External control gear included with dip-switches to select power during installation
- Refurbishment rings are available as accessory
- Selected DALI 2.0 driver available as accessory

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	UI SP DK FIX P
	Addon Technical Information	Light source Insert SP DK FIX P PS DIM IP44
	Addon Technical Information	Dimmerlist SPOT GEN2
	Legal information	Legal Insert
	Declarations of conformity	CE Declaration of Conformity SPOT DIM
	Declarations Of Conformity UKCA	UKCA Declaration of Conformity SPOT DIM
	Declarations Of Conformity UKCA	SP DIM
	Certificates	SP GEN2

Photometric and lighting design files		Document name
	IES file (IES)	SP DK FIX P 8W 930 PS DIM IP44 BK
	LDT file (Eulumdat)	SP DK FIX P 8W 930 PS DIM IP44 BK
	ULD file (DIALux)	SP DK FIX P 8W 930 PS DIM


Photometric and lighting design files		Document name
	ROLF file (RELUX)	SP DK FIX P 8W 930 PS DIM
	UGR file (UGR table)	SP DK FIX P 8W 930 PS DIM IP44 BK
	LDC typ cone	SP DK FIX P 8W 930 PS DIM IP44 BK
	LDC typ polar	SP DK FIX P 8W 930 PS DIM IP44 BK
CAD/BIM files		Document name
	BIM_Revit_3D	SP DK FIX G2
	CAD_STEP_3D	SP DK FIX
Tender texts		Document name
	Tender documents	SPOT DARKLIGHT 8W 930 PS DIM IP44 BK-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075799868	Folding box 1	100 mm x 105 mm x 105 mm	486.00 g	1.10 dm ³
4058075799875	Shipping box 20	550 mm x 215 mm x 235 mm	10888.00 g	27.79 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



	☒	☒	☒	☐
	ON	ON	ON	Preset
	1 2	1 2	1 2	1 2
	Current (CC)	85 mA	140 mA	180 mA
	Power	4 W	6 W	8 W
% rated lumen		50 %	80 %	100 %

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.