

# PRODUCT DATASHEET

## LED WORKLIGHT VALUE TRIPOD 1x30W 865

WORKLIGHT VALUE TRIPOD | Versatile LED worklight with tripod stand in value class



### Areas of application

- Renovation
- Garages
- Workshops
- Basement

### Product benefits

- Foldable for easy storage
- Portable worklight for flexible applications

### Product features

- Available with 1 or 2 luminaire heads
- Rotation angle luminaire head: 360°, swiveling: 180°
- Type of protection, luminaire head and housing: IP65/IP54, Type of protection, plug: IP44
- Height adjustment of tripod up to 1.8 m total height



## TECHNICAL DATA

## Electrical data

Nominal wattage	30.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	130.000 mA
Inrush current	4.9 A
Inrush current time $T_{h50}$	0.5 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	98
Max. number of luminaires per miniature circuit breaker C16	98
Power factor $\lambda$	$\geq 0.90$
Protection class	I
Operating mode	Integrated LED driver

## Photometrical data

Luminous flux	3000 lm
Total luminous flux of contained light sources	3500 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	< 6 sdcm
Luminous intensity	1100 cd
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.9
Photobiological safety group acc. to EN62778	RG1
Beam angle	115 °

## Dimensions &amp; Weight

Length	1050.00 mm
Width	910.00 mm
Height	1402.00 mm
Product weight	2750.00 g



## LED WORKLIGHT VAL 1X30W 865 TRIPOD

### Materials & Colors

Product color	Black/Gray
Housing color	Black/Gray
Body material	Aluminum
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type F
Type of protection	IP54
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Standing
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE
Luminaire with limited surface temperature, "D sign"	No

### Additional product data

Number of illuminants	empty
-----------------------	-------

## EQUIPMENT / ACCESSORIES

- 1,5m power cable for flexible installation

## DOWNLOAD DATA

Documents and certificates	Document name
 PDF	User Instruction
 PDF	Legal information
 PDF	Declarations of conformity

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075831391	Folding box 1	158 mm x 228 mm x 787 mm	3096.00 g	28.35 dm <sup>3</sup>
4058075831407	Shipping box 2	802 mm x 243 mm x 341 mm	7157.00 g	66.46 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.