



# PRODUCT DATASHEET

## FLASHLIGHT TACTICAL IP65

FLASHLIGHT TACTICAL IP65 | Outdoor mobiles

---

### Areas of application

- Multifunctional



---

### Product benefits

- 4 operating modes: 1 press: bright light 1400 lm, 2nd press: soft light 450 lm, 3rd press: SOS mode, 4th press: flashing mode
- The angle of the light beam is adjusted by turning the lens
- 4 hours of running at full brightness
- Powered by 6 AAA batteries (not included)
- Type of protection: IP65 (with closed rotary lens adjustment mechanism)

---

### Product features

- Sturdy aluminum housing
- Convenient button for switching modes

## TECHNICAL DATA

### Electrical data

|                               |         |
|-------------------------------|---------|
| Nominal wattage               | 15.00 W |
| Inrush current                | 1.8 A   |
| Inrush current time $T_{h50}$ | 0.5 s   |
| Operating mode                | Battery |

### Photometrical data

|                           |            |
|---------------------------|------------|
| Luminous flux             | 1400 lm    |
| Luminous efficacy         | 93 lm/W    |
| Color temperature         | 6500 K     |
| Light color (designation) | Cool White |
| Color rendering index Ra  | 70         |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 50.00 mm  |
| Height         | 197.00 mm |
| Product weight | 510.00 g  |

### Materials & Colors

|                 |          |
|-----------------|----------|
| Product color   | Black    |
| Housing color   | Black    |
| Body material   | Aluminum |
| Mercury content | 0.0 mg   |

### Application & Mounting

|                           |                 |
|---------------------------|-----------------|
| Ambient temperature range | -20...+40 °C    |
| Type of protection        | IP65/IP20       |
| Dimmable                  | No              |
| Adjustable                | No              |
| LED module replaceable    | Not replaceable |
| With light source         | Yes             |

### Lifespan

|                           |                       |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h <sup>1)</sup> |
|---------------------------|-----------------------|

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|           |           |
|-----------|-----------|
| Standards | CE / UKCA |
|-----------|-----------|

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854175848 | Folding box<br>1             | 59 mm x 59 mm x 206 mm               | 536.00 g     | 0.72 dm <sup>3</sup>  |
| 4099854175855 | Shipping box<br>24           | 367 mm x 253 mm x 235 mm             | 13513.00 g   | 21.82 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.