

Product Name

Integra L

Technical description

The brand new generation of Lanzini floodlight is the result of a deep design activity combined with the latest lighting technology. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket. Screws made of AISI 304 stainless steel. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic in optical PC.

Supply

Driver mounted into the fitting. Available in ON-OFF, dimmable or DALI
 Input voltage 220 - 240V AC 50/60Hz.
 Temperature -40° +45°

Installation

Wall and ceiling

Applications

Commercial Areas, Parking, Sport facilities, Zone de production

Size (mm)



269 x 348 x 55

Colour

Dark grey **4**

Decay of the luminous flux

≥100.000 hr L90B10



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L0INL40S7BL40120	LED	120 W	17507 lm	19200 lm	4000 K	>80	S7	Dark Grey	-
L0INL40S7DI40120	LED	120 W	17507 lm	19200 lm	4000 K	>80	S7	Dark Grey	Dimmer
L0INL40S7DA40120	LED	120 W	17507 lm	19200 lm	4000 K	>80	S7	Dark Grey	DALI

Accessories

Cable with connector Ca. 2m/Co. IP 2 poli LKITA000000000040 Ca. 2m/Co. IP 3 poli LKITA000000000041	Fast connector IP 2 poles LKITA000000000017	Fast connector IP 3 poles LKITA000000000003	Grid kit IK10 protection LKITA000000000042	Laser pointer support kit LKITA000000000093	Pole connection B LKITA00000040109

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.