

> Datasheet - AMENITY - WAP

WAP.1.LA034.HA.C7.C.LRD.CTR.NLD



Product image may not represent the final configuration stated above.



<https://www.holophane.co.uk/>



T +44 (0)1908 649 292

E info@holophane.co.uk

Holophane Europe Limited
Bond Avenue, Milton Keynes
Buckinghamshire MK1 1JG
United Kingdom

Product Specification




WAP Holophane Website

Holophane Wallpack LED bulkhead luminaire, manufactured from marine grade die-cast aluminium with integrated thermal management design. LED light engine modules are IP65 with individual PMMA lenses. Luminaire housing sealed to IP65 and suitable for wall mounting with rear, top, bottom and side via threaded 3/4 inch cable entry/exit points. International Dark-Sky Association Approved (colour temperatures 3000K or warmer are approved under the IDA)

This specific SKU includes:

- Series 1
- LED light engine producing c.3,000 lm with a nominal 4000K colour temperature
- High beam asymmetric distribution
- Black (RAL9005)
- Enhanced paint finish
- DALI enabled (any on site controls wiring should be completed in compliance with the respective control system's installation instructions (and limitations). Holophane cannot be held responsible for the operation of its luminaires with third party control systems)
- Conduit Thread Reducer Adapter from 3/4 inch NPT to 20mm (2 supplied in box)



Performance

Drive Current from Driver:	692mA
Power:	23W
Fitting Current:	0.1A
Power Factor:	0.97
Fitting Inrush:	15A - 0.295ms
Number of Drivers:	1
1x Driver 1 Inrush:	15A - 0.295ms
Max Drivers per 16A Type B MCB:	29
Max Fittings per 16A Type B MCB:	29
Total Number of LEDs:	10
Minimum Dim Level:	8 %




10Kg



[Installation Guide](#)

Dimensions



CIBSE TM66 - CEAM Rating

2.4*

2.5 to 4.0	1.5 to 2.5	0.5 to 1.5	0 to 0.5
Excellent circularity	Definite/ substantial progress to circularity	Some circular economy functionality	Very poor circular economy performance

*Preliminary Rating

<https://www.holophane.co.uk/>




T +44 (0)1908 649 292

E info@holophane.co.uk


Holophane Europe Limited
Bond Avenue, Milton Keynes
Buckinghamshire MK11JG
United Kingdom

Photometry IES File

Polar Plot




Isoilluminance Plot



Lumens:	2,720
CCT:	4000K
CRI:	70
IES File:	WAP.1.LA034.HA

LLMF Graph



For reference purposes, the graph extrapolates beyond the recommend 6x LM-80 data in TM-21, which our calculations are based on.

Colour Temperatures



Colours

Selected Colour

	C7	Textured Black (RAL9005)
--	-----------	--------------------------

Custom Colour Available


	RAL****	Customer specified colour
--	----------------	---------------------------

*Choosing a custom colour may increase the cost and lead time.

Standard Colours Available

	C1	Smooth White (RAL9016)
---	-----------	------------------------

	C4	Smooth Graphite (RAL7011)
---	-----------	---------------------------

	C6	Smooth Grey (RAL7035)
---	-----------	-----------------------

	C7	Textured Black (RAL9005)
---	-----------	--------------------------

	C9	Metallic Silver (RAL9006)
---	-----------	---------------------------

Lumen data is considered to be representative of the configuration shown, and may vary, with a tolerance on flux of +/- 7% (typical of LED manufacturer's data) and luminaire power of +/- 5%.

The specifications of the Holophane luminaires represents typical values. All descriptions, illustrations, drawings and specifications in the Holophane catalogue, Datasheets and website represent only general particulars of the goods to which they apply and shall not form part of any contract. The company reserves the right to change specifications at its discretion without prior notification or public announcement.