


0153010	<b>DATA SHEET</b>	
Valid from: 01.04.2019	<b>DIN compensating cable KP 9 L 2x1,5 round</b>	

## Application

The compensating cable KP 9 L 2 x 1,5 mm<sup>2</sup> is a PVC insulated cable which transmits the thermoelectric voltage of PtRh/Pt thermocouples. It is for flexible use and fixed installation in dry and damp rooms. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range.

## Design

Conductor	1.5 mm <sup>2</sup> (48 x 0.20 mm)
Conductor material	RCB/SCB alloying, accuracy class 2 according DIN 43722
	Positive conductor: Cu (copper)
	Negative conductor: CuNi (cupronickel)
Core insulation	PVC compound
Core identification	Positive conductor: red
	Negative conductor: white
Core layering	Cores twisted together
Outer sheath	PVC compound, colour: white

## Electrical properties

Limiting deviation class 2	±60 µV (±5.0 °C) / measuring point temperature +1000 °C
----------------------------	---

## Mechanical and thermal properties

Temperature range	occasional flexing: -5 °C up to +70 °C
Minimum bending radius	occasional flexing: 12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2

Creator: TOME/PCM Released: ALTE/PDC	Document: DB0153010EN Version: 02	Page 1 of 1
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.

PD 0019/05\_04.18EN